

## HY-ALERTA™ 600 Fixed Area Hydrogen Monitor

### Description

H2scan's HY-ALERTA™ 600 Fixed Area Hydrogen Monitor will provide hydrogen-specific leak detection and measurement for hydrogen concentrations as low as 4000 ppm and can be scaled to any concentration up to 5% hydrogen by volume, a range representing 10% to 125% of hydrogen's low flammability limit. The monitor is designed for either ceiling or wall mount and has an RS422 capability that extends the interface from the sensor to the controller to several hundred feet. H2scan's hydrogen-specific sensor technology has no cross sensitivity to any other combustible gases, thus eliminating false positive alarms and increasing system reliability.

### Performance

Hydrogen Sensitivity Range:  
0.4% to 5.0% hydrogen by volume,  
10% to 125% hydrogen lower flammable limit  
Accuracy:  $\pm (0.03 \times \text{indication} + 0.2)$  percent  
hydrogen by volume  
Typical Response Time: T90 of 60 sec maximum  
Ingress Protection: IP64 capable  
Calibration Interval: 90 days  
Product Life Expectancy: 10 years

### Interface Options

Input Voltage Range: 8 VDC to 13 VDC  
Input Current: 1.0 A  
Analog Outputs:  
Output Voltages - OR - Output Currents  
• 0 VDC to 5 VDC • 4 mA to 20 mA  
• 1 VDC to 5 VDC • 0 mA to 20 mA  
• 0 VDC to 4 VDC • User-specific mA range  
• 0.5 VDC to 4.5 VDC  
• User-specific VDC range  
Serial Communication Options: RS232 or RS422  
Relay Contacts: Two programmable 60 VDC / 1 A  
SPDT relays with both normally open (N.O.)  
and normally closed (N.C.) contacts.

### Operating Conditions

Operating Temperature Range: -20°C to 40°C  
Storage Temperature Range: -40°C to 50°C  
Operating Humidity: 0% to 95% RH  
Calibration Background Gas: Air

### Dimensions

Total Length: 7.2 in.  
Mounting Bracket Length: 5.6 in.  
Total Width: 4.4 in.  
Mounting Bracket Width: 4.0 in.  
Depth: 1.6 in.

**Certifications:**  US LISTED 

